



City of Campbell
70 North First Street
Campbell, CA 95008 -1423

Project Image



Notice of Decision on Proposed Project

Dear Campbell Resident,

February 27, 2024

The Community Development Director will be rendering a decision on the following project.

Project Address: 401 Dallas Drive

Zoning | Area Plan: R-1-8 | CVNP

Neighborhood Association(s): CVNPA

Council District: 1

File No.: PLN-2023-176

APN: 412-39-013

Applicant: Gkw Architects, Inc.

Property Owner: AB Commercial Property Management

Application Type: Administrative Site and Architectural Review Permit

Project Planner: Larissa Lomen, Assistant Planner

Project Description:

To allow the demolition of the existing single-family dwelling and the construction of a new approximately 4,086 square foot single family dwelling.

Comment Period:

You have the opportunity to provide comment prior to the Director's decision.

The ten-day comment period for this application begins on **February 28, 2024**. If you have comments regarding this application must be submitted in writing (including email) to the Planning Division before 5:00 p.m. on **March 8, 2024**. The Director will then consider all comments submitted within this time period prior to a decision. No additional notice will be provided.

Decision by the Community Development Director is final unless an appeal is received in writing within 10 days of the decision or submitted in writing to the City of Campbell Community Development Department, 70 N. First Street, Campbell, prior to the end of the appeal period. If you have questions or comments regarding this application you may contact the Project Planner.





- City of Campbell -
Community Development Department
70 N. First Street, Campbell CA 95008
(408)866-2140 | planning@campbellca.gov

Note: Applications may change after initial application submittal.
To view the project plans, please scan the QR code.

**Asistencia en Español disponible,
Simplemente marque (408) 866-2140 y pida traduccion en Español



SCOPE OF WORK	3D MODEL
<ul style="list-style-type: none"> DEMO EXISTING RESIDENCE (1,750 SF) NEW CONSTRUCTION OF TWO STORY SINGLE-FAMILY RESIDENCE (4,086 SF) 	
PROJECT DIRECTORY	VICINITY MAP
OWNER: AB COMMERCIAL PROPERTY MANAGEMENT, LLC BY ALFREDO BARAJAS 401 DALLAS DRIVE, CAMPBELL, CA 95008 RE.INVESTOR@HOTMAIL.COM, 408-605-4800	
ARCHITECT: GKW ARCHITECTS, INC. GORDON K WONG, AIA, NCARB, LEED GA 710E MCGILVERY LANE SUITE 109, CAMPBELL, CA 95008 GORDONKWONG@GKWARCHITECTS.COM, 408-796-1845	
LAND SURVEYOR: WILSON LAND SURVEYS, INC. KEN WILSON 261 CARLTON COURT, LOS GATOS, CA 95032 (408) 427-2278 KEN@WILSONLANDSURVEYS.COM	
CIVIL ENGINEER: GREEN CIVIL ENGINEERING, INC. AMBROSE CHIN HANG WONG 1900 S NORFOLK ST #350, SAN MATEO, CA 94403 (650) 931-2514 INFO@GREEN-CE.COM	
STRUCTURAL ENGINEER: TBD	
T24 ENERGY REPORT: CARSTAIRS ENERGY INC. TIMOTHY CARSTAIRS 2238 BAYVIEW HEIGHTS DRIVE, SUITE E, LOS OSOS, CA 93402 TITLE24@YAHOO.COM, 805-904-8048	
GEOTECHNICAL: TBD	
JURISDICTION: CITY OF CAMPBELL PLANNING & BUILDING DEPARTMENTS 70 N FIRST ST, CAMPBELL, CA 95008 PLANNING@CITYOFCAMPBELL.COM, 408-866-2140	
SANITATION: WEST VALLEY SANITATION DISTRICT 100 EAST SUNNYOAKS AVENUE, CAMPBELL, CA 95008 INFO@WESTVALLEYSAN.ORG, 408-378-2407	

PROJECT INFORMATION	SHEET INDEX																																																						
PROJECT LOCATION: 401 DALLAS DRIVE, CAMPBELL CA 95008 APN: 412-39-013 TRACT NO. / LOT: 973 / 120 ZONING: R-1-8 (SINGLE FAMILY RESIDENTIAL) LOT AREA: 9,540.75 SF LOT WIDTH: 75.00' EXISTING USE: ONE STORY SINGLE FAMILY PROPOSED USE: TWO STORY SINGLE FAMILY CONSTRUCTION TYPE: V-B SPRINKLERED FAR SF CALC. ALLOWED: 9,540.75 X 45% = 4293.34 SF (P) FAR SF: 4,086 SF / 9,540.75 SF = 42.83% = COMPLIANT HEIGHT LIMIT: (MAX) 35'-0" / 2.5 STORIES; (P) 28'-5 1/2" / 2 STORIES = COMPLIANT	<table border="1"> <thead> <tr> <th>Sheet Number</th> <th>Sheet Name</th> </tr> </thead> <tbody> <tr> <td colspan="2">General</td> </tr> <tr> <td>G000</td> <td>General, Project Info & Site Plan, Proposed</td> </tr> <tr> <td>G001</td> <td>General, Abbreviation, Notes & Site Plan, Existing</td> </tr> <tr> <td>G002</td> <td>General, Site Photography & Streetscape, Proposed</td> </tr> <tr> <td>G005</td> <td>General, Fire Department & Public Works Conditions of Approval</td> </tr> <tr> <td colspan="2">Survey</td> </tr> <tr> <td>SB</td> <td>Survey, Boundary & Topographic Survey</td> </tr> <tr> <td colspan="2">Civil</td> </tr> <tr> <td>C1</td> <td>Civil, Grading & Drainage Plan</td> </tr> <tr> <td>C2</td> <td>Civil, Utility Plan</td> </tr> <tr> <td>C3</td> <td>Civil, Detail Sheet</td> </tr> <tr> <td>C4</td> <td>Civil, Blueprint For a Clean Bay</td> </tr> <tr> <td colspan="2">Landscape</td> </tr> <tr> <td>L1</td> <td>Landscape, Master Planting Plan</td> </tr> <tr> <td>L2</td> <td>Landscape, Hydrozone Plan & WELO Calculations</td> </tr> <tr> <td>L3</td> <td>Landscape, Irrigation Plan</td> </tr> <tr> <td>L4</td> <td>Landscape, Soil Management Report</td> </tr> <tr> <td colspan="2">Architectural</td> </tr> <tr> <td>A100</td> <td>Architectural, Floor Plan, 1st & 2nd Level, Proposed</td> </tr> <tr> <td>A101</td> <td>Architectural, Roof Plan, Proposed</td> </tr> <tr> <td>A102</td> <td>Architectural, Area Diagrams</td> </tr> <tr> <td>A200</td> <td>Architectural, Elevations, Front & Back, Proposed</td> </tr> <tr> <td>A201</td> <td>Architectural, Elevations, Right & Left, Proposed</td> </tr> <tr> <td>A300</td> <td>Architectural, Cross Sections, AA & BB</td> </tr> <tr> <td>A301</td> <td>Architectural, Cross Sections, CC & DD</td> </tr> <tr> <td>A600</td> <td>Architectural, 3D Model</td> </tr> </tbody> </table>	Sheet Number	Sheet Name	General		G000	General, Project Info & Site Plan, Proposed	G001	General, Abbreviation, Notes & Site Plan, Existing	G002	General, Site Photography & Streetscape, Proposed	G005	General, Fire Department & Public Works Conditions of Approval	Survey		SB	Survey, Boundary & Topographic Survey	Civil		C1	Civil, Grading & Drainage Plan	C2	Civil, Utility Plan	C3	Civil, Detail Sheet	C4	Civil, Blueprint For a Clean Bay	Landscape		L1	Landscape, Master Planting Plan	L2	Landscape, Hydrozone Plan & WELO Calculations	L3	Landscape, Irrigation Plan	L4	Landscape, Soil Management Report	Architectural		A100	Architectural, Floor Plan, 1st & 2nd Level, Proposed	A101	Architectural, Roof Plan, Proposed	A102	Architectural, Area Diagrams	A200	Architectural, Elevations, Front & Back, Proposed	A201	Architectural, Elevations, Right & Left, Proposed	A300	Architectural, Cross Sections, AA & BB	A301	Architectural, Cross Sections, CC & DD	A600	Architectural, 3D Model
Sheet Number	Sheet Name																																																						
General																																																							
G000	General, Project Info & Site Plan, Proposed																																																						
G001	General, Abbreviation, Notes & Site Plan, Existing																																																						
G002	General, Site Photography & Streetscape, Proposed																																																						
G005	General, Fire Department & Public Works Conditions of Approval																																																						
Survey																																																							
SB	Survey, Boundary & Topographic Survey																																																						
Civil																																																							
C1	Civil, Grading & Drainage Plan																																																						
C2	Civil, Utility Plan																																																						
C3	Civil, Detail Sheet																																																						
C4	Civil, Blueprint For a Clean Bay																																																						
Landscape																																																							
L1	Landscape, Master Planting Plan																																																						
L2	Landscape, Hydrozone Plan & WELO Calculations																																																						
L3	Landscape, Irrigation Plan																																																						
L4	Landscape, Soil Management Report																																																						
Architectural																																																							
A100	Architectural, Floor Plan, 1st & 2nd Level, Proposed																																																						
A101	Architectural, Roof Plan, Proposed																																																						
A102	Architectural, Area Diagrams																																																						
A200	Architectural, Elevations, Front & Back, Proposed																																																						
A201	Architectural, Elevations, Right & Left, Proposed																																																						
A300	Architectural, Cross Sections, AA & BB																																																						
A301	Architectural, Cross Sections, CC & DD																																																						
A600	Architectural, 3D Model																																																						
PRIMARY SETBACKS FRONT: 20'-0" GARAGE: 25'-0" LEFT SIDE: 5 FEET OR 50% OF THE BUILDING WALL HT. (14'-0" x 0.5 = 7'-0"), WHICHEVER IS GREATER, SO THE LEFT SETBACK IS 7'-0" FEET. RIGHT SIDE: 5 FEET OR 50% OF THE BUILDING WALL HT. (21'-0" x 0.5 = 10'-6"), WHICHEVER IS GREATER, SO THE RIGHT SETBACK IS 10'-6" FEET. REAR: 20 FT OR 15% OF LOT DEPTH (127.18' x 0.15 = 19.077'), WHICHEVER IS LESSER, SO THE REAR SETBACK IS 19'-0 3/4" FEET. OCCUPANCY: R-3 BUILDING SIZE (P) PRIMARY HOUSE 3,466 SF 1ST FLOOR 2,198 SF 2ND FLOOR 1,268 SF (P) ATTACHED 2-CAR GARAGE 486 SF (P) TOTAL RESIDENCE 3,952 SF (P) TOTAL PORCH AREA (DOES NOT COUNT AS FLOOR AREA) FRONT PORCH 205 SF REAR PORCH 420 SF TOTAL 625 SF LOT COVERAGE CALCULATIONS (REFER TO G001 FOR COVERAGE DIAGRAM) (P) TOTAL COVERAGE 2,694 SF 2,694 SF / 9,540.75 SF = 28.24% MAX LOT COVERAGE 45%, 28.24% < 45% (OK)																																																							

DEFERRED SUBMITTAL	PUBLIC WORKS & SITE PLAN NOTES
<ol style="list-style-type: none"> AN AUTOMATIC FIRE SPRINKLER SYSTEM SHALL BE INSTALLED AS A DEFERRED SUBMITTAL IN BOTH SINGLE FAMILY RESIDENCE AND THE DETACHED ADU A PERMIT FOR A NFPA 13D RESIDENTIAL FIRE SUPPRESSION SPRINKLER SYSTEM SHALL BE APPLIED FOR AS A DEFERRED SUBMITTAL. SUBMIT CALCULATIONS AND DESIGN DIRECT TO SANTA CLARA COUNTY FIRE DEPARTMENT (SCCFD), 14700 WINCHESTER BLVD, LOS GATOS (408) 378-4010. THE DEFERRED SUBMITTAL MUST BE APPLIED FOR, AND APPROVED, BEFORE ANY ROUGH INSPECTIONS ARE MADE. 	<ol style="list-style-type: none"> CONTRACTOR IS RESPONSIBLE FOR DUST CONTROL AND INSURING AREA ADJACENT TO WORK IS LEFT IN A CLEAN CONDITION. UTILIZE BEST MANAGEMENT PRACTICES (BMPs), AS REQUIRED BY THE STATE WATER RESOURCES BOARD, FOR ANY ACTIVITY, WHICH DISTURBS SOIL. CONTRACTOR IS RESPONSIBLE FOR TEST, INSPECTIONS AND PROCEDURAL REQUIREMENTS PER CITY OF CAMPBELL. OPERABLE SMOKE DETECTORS MUST BE IN PLACE PRIOR TO RE-OCCUPY DWELLINGS PER CITY OF CAMPBELL CODES. PLUMBING & ELECTRICAL SURVEY REQUIRED FOR METER RELEASE. ADDITIONS, ALTERATIONS OR REPAIRS SHALL CONFORM TO ANY BUILDING OR STRUCTURE WITHOUT REQUIRING THE EXISTING BUILDING OR STRUCTURE TO COMPLY WITH ALL THE REQUIREMENTS OF THE CBC, PROVIDED THE ADDITION, ALTERATION, OR REPAIR CONFORMS TO THAT REQUIRED FOR NEW BUILDING OR STRUCTURE PER CBC SECTION 3403.2 CONTRACTOR TO VERIFY SIZE & LOCATION OF ALL UTILITY CONNECTIONS. CONTRACTOR TO PROVIDE ALL NEW UTILITY CONNECTIONS AND/OR UPGRADE EXISTING AS REQUIRED. CONTRACTOR SHALL OBTAIN ALL NECESSARY PERMITS AND APPROVALS AS REQUIRED BY GOVERNING AGENCIES. CONTRACTOR SHALL OBTAIN ALL NECESSARY DEMOLITION PERMITS AND APPROVALS INCLUDING ASBESTOS ABATEMENT AS PART OF THE BASE BID PER CGSBC 301.1.1 - RESIDENTIAL BUILDINGS UNDERGOING PERMITTED ALTERATIONS, ADDITIONS OR IMPROVEMENT SHALL REPLACE NONCOMPLIANT PLUMBING FIXTURES WITH WATER-CONSERVING PLUMBING FIXTURES. PLUMBING FIXTURES REPLACEMENT IS REQUIRED PRIOR TO ISSUANCE OF A CERTIFICATE OF FINAL COMPLETION, CERTIFICATE OF OCCUPANCY OR FINAL PERMIT APPROVAL BY THE LOCAL BUILDING DEPARTMENT. PER CGSBC 301.1.1 - WHERE ADDITION OR ALTERATION INCREASED THE BUILDING'S CONDITIONED AREA, VOLUME, OR SIZE, THE REQUIREMENTS OF CALGREEN CHAPTER 4 SHALL APPLY ONLY TO AND WITHIN THE SPECIFIC AREA OF THE ADDITION OR ALTERATION.

APPLICABLE CODES	REQUIRED NOTES
<ul style="list-style-type: none"> 2022 CALIFORNIA BUILDING CODE 2022 CALIFORNIA RESIDENTIAL CODE 2022 CALIFORNIA MECHANICAL CODE 2022 CALIFORNIA PLUMBING CODE 2022 CALIFORNIA ELECTRICAL CODE 2022 CALIFORNIA ENERGY CODE 2022 CALIFORNIA FIRE CODE 2022 CALIFORNIA GREEN BUILDING STANDARDS CODE CITY OF CAMPBELL MUNICIPAL CODE ALL OTHER STATE AND LOCAL LAWS, ORDINANCES AND REGULATIONS 	<p>PLANNING FINAL REQUIRED, THE NEW LANDSCAPING INDICATED ON THE PLANS MUST BE INSTALLED PRIOR TO FINAL INSPECTION, CHANGES TO THE LANDSCAPING PLAN REQUIRE PLANNING APPROVAL</p>


BARAJAS RESIDENCE

CAMPBELL — CALIFORNIA




1 Site Plan, Proposed
1/8" = 1'-0"

General, Project Info & Site Plan, Proposed



GORDON K WONG, ARCHITECT LIC# 34463
1000 WILSON AVENUE SUITE 109
CAMPBELL, CA 95008
GORDONKWONG@GKWARCHITECTS.COM

GORDON K WONG, ARCHITECT LIC# 34463
1000 WILSON AVENUE SUITE 109
CAMPBELL, CA 95008
GORDONKWONG@GKWARCHITECTS.COM



NEW SINGLE FAMILY RESIDENCE
401 DALLAS DRIVE
CAMPBELL, CA 95008

Revision Schedule	
1	25.12.06 Planning

General, Project Info & Site Plan, Proposed

G000

SCALE AS INDICATED

2/7/2024 10:36:33 AM



1_FRONT RIGHT



3_FRONT SIDE



5_REAR LEFT




2_FRONT LEFT



4_REAR RIGHT



6_REAR SIDE



① Site Plan, Existing, Key Plan
1/16" = 1'-0"



② Elevation, Front, Proposed for Streetscape
1/8" = 1'-0"



JOSHUALI & KEVIN YU, PROJECT DESIGNERS
1000 WILSON AVENUE SUITE 100
CAMPBELL, CA 95008
JOSHUALI@GKWARCHITECTS.COM

GORDON K WONG, ARCHITECT LIC# 34058
1000 WILSON AVENUE SUITE 100
CAMPBELL, CA 95008
GORDONWONG@GKWARCHITECTS.COM



General, Site Photography & Streetscape, Proposed

NEW SINGLE FAMILY RESIDENCE
401 DALLAS DRIVE
CAMPBELL, CA 95008

Revision Schedule

NO.	DATE	DESCRIPTION

General, Site Photography & Streetscape, Proposed

G002

SCALE AS INDICATED

2/7/2024 10:37:38 AM

MEMORANDUM CITY OF CAMPBELL

TO: Larissa Lomen, Project Planner DATE: 11/09/23
FROM: Arlyn Villanueva, Project Engineer
SUBJECT: DRC APPLICATION

Site Address: 401 Dallas Drive
For File No(s): PLN-2023-176
Project Description: Use permit to allow the construction of a new 4086-sf single family dwelling.
Applicant: Gordon Wong, GKW Architects, Inc.

The subject request may be found:

- Complete
Incomplete

PUBLIC WORKS DEPARTMENT CONDITIONS OF APPROVAL

- 1. The scope of this project triggers the requirement for Frontage Improvements as required by Campbell Municipal Code 11.24.040.
2. Storm Drain Area Fee: Prior to issuance of any grading or building permits for the site, the applicant shall pay the required Storm Drain Area fee, currently set at \$2,120.00 per net acre, which is \$464.28 (set for R-1 land use).
3. Stormwater Pollution Prevention Measures: Prior to issuance of any grading or building permits, the applicant shall comply with the National Pollution Discharge Elimination System (NPDES) permit requirements, Santa Clara Valley Water District requirements, and the Campbell Municipal Code regarding stormwater pollution prevention.

401 Dallas Drive (PLN-2023-176)

Resources to achieve these objectives include Stormwater Best Management Practices Handbook for New Development and Redevelopment ("CA BMP Handbook") by the California Stormwater Quality Association (CASQA), 2003; Start at the Source: A Design Guidance Manual for Stormwater Quality Protection ("Start at the Source") by the Bay Area Stormwater Management Agencies Association (BASMAA), 1999; and Using Site Design Techniques to Meet Development Standards for Stormwater Quality: A Companion Document to Start at the Source ("Using Site Design Techniques") by BASMAA, 2003.

- 4. Water Meter(s) and Sewer Cleanout(s): Proposed water meter(s) and sewer cleanout(s) shall be relocated or installed on private property behind the public right-of-way line.
5. Plans / Encroachment Permit / Fees / Deposits: Prior to issuance of any grading or building permits for the site, the applicant shall cause plans for public street improvements to be prepared, pay various fees and deposits, and provide insurance necessary to obtain an encroachment permit for construction of the standard public street improvements, as required by the City Engineer.
6. Street Improvements Completed for Occupancy and Building Permit Final: Prior to allowing occupancy and/or final building permit signoff for any and/or all buildings, the applicant shall have the required street improvements installed and accepted by the City, and the design engineer shall submit as-built drawings to the City.
7. Utility Encroachment Permit: Separate encroachment permits for the installation of utilities to serve the development will be required (including water, sewer, gas, electric, etc.).



DEVELOPMENTAL REVIEW COMMENTS

Plans and Scope of Review: This project shall comply with the following: The California Fire (CFC) & Building (CBC) Code, 2022 edition, as adopted by the City of Campbell Municipal Code (CMC) and California Code of Regulations (CCR).

The scope of this project includes the following: Proposed new 4,752 SF two-story single-family residence with an attached garage.

Plans Status: Plans are APPROVED with the following conditions.

Plan Review Comments: 1. Required Fire Flow: The minimum required fire flow for this project is 875 Gallons Per Minute (GPM) at 20 psi residual pressure.

2. Fire Sprinklers Required: An automatic residential fire sprinkler system shall be installed in all new one- and two-family dwellings.
3. Address Identification: New and existing buildings shall have approved address numbers, building numbers or approved building identification placed in a position that is plainly legible and visible from the street or road fronting the property.

4. Water Supply Requirements: Potable water supplies shall be protected from contamination caused by fire protection water supplies. It is the responsibility of the applicant and any contractors and subcontractors to contact the water purveyor supplying the site of such project, and to comply with the requirements of that purveyor.

5. Construction Site Fire Safety: All construction sites must comply with applicable provisions of the CFC Chapter 33 and our Standard Detail and Specification S1-7. Provide appropriate notations on subsequent plan submittals, as appropriate to the project. CFC Chp. 33.

This review shall not be construed to be an approval of a violation of the provisions of the California Fire Code or of other laws or regulations of the jurisdiction. A permit presuming to give authority to violate or cancel the provisions of the fire code or other such laws or regulations shall not be valid. Any addition to or alteration of approved construction documents shall be approved in advance [CFC, Ch. 1, 105.3.6].

Table with project details: City (CBL), Plans (SPEED NEW), RMDL (AB), Occupancy (R-3/U), Const. Type (VB), Applicant (Gkw Architects), Date (11/9/2023), Page (1 of 2). Includes fields for Name of Project (SFR), Location (401 Dallas Dr Campbell), and Fire Flow/Reduction details.

Serving Santa Clara County and the communities of Campbell, Cupertino, Los Altos, Los Altos Hills, Los Gatos, Monte Sereno, and Saratoga.



DEVELOPMENTAL REVIEW COMMENTS

4. Water Supply Requirements: Potable water supplies shall be protected from contamination caused by fire protection water supplies. It is the responsibility of the applicant and any contractors and subcontractors to contact the water purveyor supplying the site of such project, and to comply with the requirements of that purveyor.
5. Construction Site Fire Safety: All construction sites must comply with applicable provisions of the CFC Chapter 33 and our Standard Detail and Specification S1-7. Provide appropriate notations on subsequent plan submittals, as appropriate to the project. CFC Chp. 33.

This review shall not be construed to be an approval of a violation of the provisions of the California Fire Code or of other laws or regulations of the jurisdiction. A permit presuming to give authority to violate or cancel the provisions of the fire code or other such laws or regulations shall not be valid. Any addition to or alteration of approved construction documents shall be approved in advance [CFC, Ch. 1, 105.3.6].

Table with project details: City (CBL), Plans (SPEED NEW), RMDL (AB), Occupancy (R-3/U), Const. Type (VB), Applicant (Gkw Architects), Date (11/9/2023), Page (2 of 2). Includes fields for Name of Project (SFR), Location (401 Dallas Dr Campbell), and Fire Flow/Reduction details.

Serving Santa Clara County and the communities of Campbell, Cupertino, Los Altos, Los Altos Hills, Los Gatos, Monte Sereno, and Saratoga.



Professional information for Gordon K Wong, Architect.

Professional information for Joshua Liu & Kevin Yu, Project Designers.



General, Fire Department & Public Works Conditions of Approval

NEW SINGLE FAMILY RESIDENCE 401 DALLAS DRIVE CAMPBELL, CA 95008

Revision Schedule

General, Fire Department & Public Works Conditions of Approval

G005

SCALE AS INDICATED

2/7/2024 10:37:39 AM

SURVEYOR'S NOTE

THIS MAP CORRECTLY REPRESENTS A SURVEY DONE BY ME OR UNDER MY DIRECTION IN CONFORMANCE WITH THE REQUIREMENTS OF THE LAND SURVEYORS ACT. THE BOUNDARY LINES SHOWN HEREON ARE BASED ON A BOUNDARY SURVEY DONE BY WILSON LAND SURVEYS.

Koen T. Wilson 08/22/2023
 KOEN T. WILSON LS 9440

SITE BENCHMARK

ELEVATIONS FOR THIS SURVEY ARE BASED ON ASSUMED ELEVATION OF 500.00' AT CONTROL POINT #1.

GENERAL NOTES

- TREE SIZES AND TYPES ARE APPROXIMATE AND SHOULD BE VERIFIED BY A CERTIFIED ARBORIST.
- FINISH FLOOR ELEVATIONS ARE TAKEN AT DOOR THRESHOLDS.
- BUILDING CORNERS WERE LOCATED AT FINISH LOCATIONS (STUCCO, BLOCK OR WOOD AS IT EXISTS IN THE FIELD).
- LOCATIONS OF ALL EXISTING ONSITE FEATURES (WITH THE EXCEPTION OF THE EXISTING BUILDING) SHOULD NOT BE USED AS A REFERENCE WHEN LAYING OUT NEW CONSTRUCTION.

UNDERGROUND UTILITY NOTE

UNDERGROUND UTILITY LINES, IF SHOWN, DEPICT OUR ESTIMATION OF WHERE THE ACTUAL LINES MAY BE LOCATED. THE LINES WERE DETERMINED BY CONNECTING VISIBLE UTILITY APPURTENANCES AND ALSO BY USING PAINTED MARKINGS PLACED BY OTHERS. THE UNDERGROUND UTILITIES MAY OR MAY NOT BE AS DEPICTED ON THIS SURVEY. NO LIABILITY IS ACCEPTED FOR ANY DISCREPANCIES, OMISSIONS OR ERRORS WITH REGARD TO SAID UNDERGROUND UTILITY DEPICTIONS ON THIS SURVEY.

TITLE REPORT NOTE



EASEMENTS SHOWN ARE BASED ON A TITLE REPORT PREPARED BY OLD REPUBLIC TITLE COMPANY DATED APRIL 25, 2023 (ORDER NO. 0615035174-TE)

SETBACK LINES NOTE

BUILDING SETBACK LINES WERE NOT SHOWN ON THIS MAP (EVEN IF THEY ARE SHOWN ON THE ORIGINAL TRACT MAP). THE DESIGNER SHOULD CHECK WITH THE APPROPRIATE AUTHORITY TO DETERMINE BUILDING SETBACK LINES.

LEGEND

- FOUND AS NOTED
- SET 5/8" REBAR WITH PLASTIC CAP 'WILSON L 9440'
- SET NAIL AND 1" BRASS TAG 'WILSON L 9440' IN CONCRETE
- ⊕ FIRE HYDRANT
- ⊕ WATER VALVE
- ⊕ WATER METER
- JOINT POLE
- GUYWIRE
- W — BLUE PAINT, EVIDENCE OF UNDERGROUND WATER LINE
- ⊕ ELECTRIC METER
- ⊕ GAS METER
- ⊕ MONITORING WELL
- G — YELLOW PAINT, EVIDENCE OF UNDERGROUND GAS LINE
- ⊕ A/C AIR CONDITIONING UNIT
- ⊕ UTIL UTILITY BOX
- ⊕ PH PHONE BOX
- P — EVIDENCE OF UNDERGROUND PHONE LINE
- ⊕ TV TV BOX
- OH — OVERHEAD LINE
- TV — EVIDENCE OF UNDERGROUND TV LINE
- ⊕ DROP INLET
- ⊕ M MANHOLE
- ⊕ D STORM DRAIN MANHOLE
- ⊕ S SEWER MANHOLE
- ⊕ SC SEWER CLEANOUT
- SS — GREEN PAINT, EVIDENCE OF UNDERGROUND SEWER LINE
- ⊕ SIGN
- ⊕ CONTROL POINT
- ⊕ LAMP POST
- ⊕ ELECTRIC BOX
- ⊕ COMMUNICATION BOX
- WOOD FENCE
- CONCRETE
- LO LIVE OAK
- WO WHITE OAK
- RW REDWOOD
- TYP. TYPICAL
- PROPERTY LINE
- CHAIN LINK FENCE
- P.S.E. PUBLIC SERVICE EASEMENT
- TILE
- BUILDING
- STREET CENTER LINE
- TIE LINE/EASEMENT LINE
- FF FINISH FLOOR ELEVATION



CONTROL POINTS

Point	Northing	Easting	Elevation	Description
1	4740.4338	5287.2179	500.000	CP N+T
8	4822.1257	5288.5413	501.350	CP NL
9	4779.7616	5221.4271	501.990	CP SPIKE
11	4835.0874	5218.6869	502.046	CP SPIKE

This map was prepared as an instrument of service for the preparation of plans and specifications for construction on the site shown on the map. The information shown hereon shall not be used in whole or in part for any other project without written authority of Wilson Land Surveys.

Copyright 2023 Koen T. Wilson Land Surveys. All rights reserved. Copies of this drawing shall have this notice. Any drawing using the information on this map shall contain the following: Topographic Survey by Wilson Land Surveys, Los Gatos, CA



Email: koenw@wilsonlandsurveys.com
 www.wilsonlandsurveys.com





BOUNDARY AND TOPOGRAPHIC SURVEY

AS REQUESTED BY:
GKW ARCHITECTS

LEGAL DESCRIPTION: LOT 120, TRACT 973, 40 M 34, CITY OF CAMPBELL, COUNTY OF SANTA CLARA, STATE OF CALIFORNIA

APN: 412-39-013
 DATE: AUGUST 2023
 FILENAME: P-111 DALLAS GKW TOPO
 SITE ADDRESS: 401 DALLAS DR, CAMPBELL, CA 95008

DRAWN BY: ARD	SCALE: 1"=10'	PROJECT: P-111	JOB NUMBER: P-111	SHEET: 1 OF 1
---------------	---------------	----------------	-------------------	---------------



GENERAL NOTES:

- IF ANY EXISTING STRUCTURES TO REMAIN ARE DAMAGED DURING CONSTRUCTION IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO REPAIR AND/OR REPLACE THE EXISTING STRUCTURE AS NECESSARY TO RETURN IT TO EXISTING CONDITIONS OR BETTER.
- CONTRACTOR SHALL PROTECT ALL PROPERTY CORNERS.
- CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE GOVERNING CODES AND BE CONSTRUCTED TO SAME.
- CONTRACTOR SHALL ADJUST AND/OR CUT EXISTING PAVEMENT AS NECESSARY TO ASSURE A SMOOTH FIT AND CONTINUOUS GRADE.
- CONTRACTOR SHALL ASSURE POSITIVE DRAINAGE AWAY FROM BUILDING FOR ALL NATURAL AND PAVED AREAS.
- THE CONTRACTOR IS SPECIFICALLY CAUTIONED THAT THE LOCATION AND/OR ELEVATION OF EXISTING UTILITIES AS SHOWN ON THESE PLANS IS BASED ON RECORDS OF THE VARIOUS UTILITY COMPANIES, AND WHERE POSSIBLE, MEASUREMENTS TAKEN IN THE FIELD. THE INFORMATION IS NOT TO BE RELIED ON AS BEING EXACT OR COMPLETE. THE CONTRACTOR MUST CALL THE APPROPRIATE UTILITY COMPANIES AT LEAST 72 HOURS BEFORE ANY EXCAVATION TO REQUEST EXACT FIELD LOCATION OF UTILITIES. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO RELOCATE UTILITIES WHICH CONFLICT WITH THE PROPOSED IMPROVEMENTS SHOWN ON THE PLANS.
- THE CONTRACTOR SHALL ADHERE TO ALL TERMS & CONDITIONS AS OUTLINED IN GENERAL N.P.D.E.S. PERMIT FOR STORMWATER DISCHARGE ASSOCIATED WITH CONSTRUCTION ACTIVITIES.
- UTILITY VAULTS, TRANSFORMERS, UTILITY CABINETS, CONCRETE BASES, OR OTHER STRUCTURES CANNOT BE PLACED OVER WATER MAINS/SERVICES. MAINTAIN 1' HORIZONTAL CLEAR SEPARATION FROM THE VAULTS, CABINETS & CONCRETE BASES TO EXISTING UTILITIES FOUND IN THE FIELD. IF THERE IS CONFLICT WITH EXISTING UTILITIES, CABINETS, VAULTS & BASES SHALL BE RELOCATED FROM THE PLAN LOCATION AS NEEDED TO MEET FIELD CONDITIONS. TREES MAY NOT BE PLANTED WITHIN 10' OF EXISTING WATER MAINS/SERVICES OR METERS. MAINTAIN 10' BETWEEN TREES AND WATER SERVICES, MAINS & METERS.
- CONTRACTOR SHALL REFER TO ARCH. PLANS FOR EXACT LOCATIONS OF UTILITIES SERVICES TO NEW BUILDING. COORDINATE WITH LOCAL UTILITIES COMPANIES FOR SERVICE CONNECTIONS.
- PROVIDE MINIMUM 2% SLOPE AT IMPERVIOUS AREA ADJACENT TO BUILDING & MINIMUM 5% SLOPE AT PERVIOUS AREA ADJACENT TO BUILDING.
- GROUND COVER IS PROVIDED IN AREAS WHERE THERE IS EXPOSED SOIL.

PRE & POST DEVELOPMENT PERVIOUS/IMPERVIOUS AREAS:		
AREA TYPE	EXISTING (SF)	PROPOSED (SF)
LOT AREA	9,540 SF	9,540 SF
	0.219 ACRE	0.219 ACRE
TOTAL LAND DISTURBANCE		9,540
HOUSE (ROOF)	1,600	3,710
GARAGE	2,506	N/A
PATIO/HARDSCAPE	2,659	524
DRIVEWAY	727	380
TOTAL IMPERVIOUS AREA	7,492	4,614
NET IMPERVIOUS AREA DECREASED:		2,878
GRAVEL	N/A	968
PERVIOUS AREA	2,048	3,938
TOTAL PERVIOUS AREA	2,048	4,926

EARTHWORK VOLUME:
(INCLUDES BUILDING PAD)

EARTHWORK QUANTITIES:	VOLUME (CUBIC YARD)
FILL	58
COMPACTION RATE: 15%	58 x 0.15 = 9 (ROUND UP)
TOTAL FILL	67
CUT	46
TOTAL EARTHWORK	21 (IMPORT)

CONTRACTOR SHALL ESTIMATE THEIR EARTHWORK QUANTITIES WHEN BIDDING ON THIS PROJECT

LEGEND

- = PROPERTY LINE
- = STREET CENTER LINE
- = EX. ROLLED CURB
- = EX. SPOT ELEVATION
- = FLOW DIRECTION
- = GRADE BREAK
- = FLOW LINE
- = CONCRETE SPLASH PAD

ABBREVIATIONS:

- BS = BOTTOM OF STEP
- BOW = BACK OF WALK
- BW = BOTTOM OF WALL
- C = CONCRETE
- DWY = DRIVEWAY
- EG = EXISTING GRADE
- EX = EXISTING
- EP = EDGE OF PAVEMENT
- FF = FINISHED FLOOR
- FG = FINISHED GRADE
- FL = FLOW LINE
- G = GARAGE
- GB = GRADE BREAK
- IE = INVERT ELEVATION
- L = LAWN
- LF = LINEAL FOOT
- LP = LOW POINT
- N = NEW
- P = PATIO OR PORCH
- PG = PERGOLA
- R.O.W. = RIGHT-OF-WAY
- S = SLOPE
- SD = STORM DRAIN
- SR = STRAW ROLL
- TC = TOP OF CURB
- TG = TOP OF GRATE
- TP = TOP OF PAVEMENT
- TS = TOP OF STEP
- TW = TOP OF WALL
- TYP = TYPICAL

GRADING NOTES



- MATCH EXISTING ELEVATION. GRADING LIMIT IS TO PROPERTY LINE. NO GRADING ALLOWED ON ADJACENT PROPERTIES
- DOWNSPOUT WITH CONCRETE SPLASH PAD PER DETAIL #1A/C3
- BEGIN/END SWALE PER DETAIL #2A/C3
- BEGIN/END ROLLED CURB & GUTTER PER CITY OF CAMPBELL STANDARD DETAIL. MATCH EXISTING FLOWLINE

REV.	DATE	DESCRIPTION

GRADING AND DRAINAGE PLAN
 401 DALLAS DR
 CAMPBELL, CA 95008

GREEN
 CIVIL ENGINEERING, INC.
 INFO@GREEN-CE.COM
 1900 S. NORFOLK ST. SUITE #350
 SAN MATEO, CA 94403

SCALE	
VERTICAL: 1"= AS SHOWN	HORIZONTAL: 1"= AS SHOWN
DATE: 09/30/2023	DESIGNED: HCL
DRAWN: BL	REVIEWED: HCL
JOB NO.: 20230039	SHEET C1
1 OF 4 SHEETS	



GENERAL NOTES:

- IF ANY EXISTING STRUCTURES TO REMAIN ARE DAMAGED DURING CONSTRUCTION IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO REPAIR AND/OR REPLACE THE EXISTING STRUCTURE AS NECESSARY TO RETURN IT TO EXISTING CONDITIONS OR BETTER.
- CONTRACTOR SHALL PROTECT ALL PROPERTY CORNERS.
- CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE GOVERNING CODES AND BE CONSTRUCTED TO SAME.
- CONTRACTOR SHALL ADJUST AND/OR CUT EXISTING PAVEMENT AS NECESSARY TO ASSURE A SMOOTH FIT AND CONTINUOUS GRADE.
- CONTRACTOR SHALL ASSURE POSITIVE DRAINAGE AWAY FROM BUILDING FOR ALL NATURAL AND PAVED AREAS.
- THE CONTRACTOR IS SPECIFICALLY CAUTIONED THAT THE LOCATION AND/OR ELEVATION OF EXISTING UTILITIES AS SHOWN ON THESE PLANS IS BASED ON RECORDS OF THE VARIOUS UTILITY COMPANIES, AND WHERE POSSIBLE, MEASUREMENTS TAKEN IN THE FIELD. THE INFORMATION IS NOT TO BE RELIED ON AS BEING EXACT OR COMPLETE. THE CONTRACTOR MUST CALL THE APPROPRIATE UTILITY COMPANIES AT LEAST 72 HOURS BEFORE ANY EXCAVATION TO REQUEST EXACT FIELD LOCATION OF UTILITIES. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO RELOCATE UTILITIES WHICH CONFLICT WITH THE PROPOSED IMPROVEMENTS SHOWN ON THE PLANS.
- THE CONTRACTOR SHALL ADHERE TO ALL TERMS & CONDITIONS AS OUTLINED IN GENERAL N.P.D.E.S. PERMIT FOR STORMWATER DISCHARGE ASSOCIATED WITH CONSTRUCTION ACTIVITIES.
- UTILITY VAULTS, TRANSFORMERS, UTILITY CABINETS, CONCRETE BASES, OR OTHER STRUCTURES CANNOT BE PLACED OVER WATER MAINS/SERVICES. MAINTAIN 1' HORIZONTAL CLEAR SEPARATION FROM THE VAULTS, CABINETS & CONCRETE BASES TO EXISTING UTILITIES AS FOUND IN THE FIELD. IF THERE IS CONFLICT WITH EXISTING UTILITIES, CABINETS, VAULTS & BASES SHALL BE RELOCATED FROM THE PLAN LOCATION AS NEEDED TO MEET FIELD CONDITIONS. TREES MAY NOT BE PLANTED WITHIN 10' OF EXISTING WATER MAINS/SERVICES OR METERS. MAINTAIN 10' BETWEEN TREES AND WATER SERVICES, MAINS & METERS.
- CONTRACTOR SHALL REFER TO ARCH. PLANS FOR EXACT LOCATIONS OF UTILITIES SERVICES TO NEW BUILDING. COORDINATE WITH LOCAL UTILITIES COMPANIES FOR SERVICE CONNECTIONS.
- PROVIDE MINIMUM 2% SLOPE AT IMPERVIOUS AREA ADJACENT TO BUILDING & MINIMUM 5% SLOPE AT PERVIOUS AREA ADJACENT TO BUILDING.
- GROUND COVER IS PROVIDED IN AREAS WHERE THERE IS EXPOSED SOIL.

LEGEND

---	PROPERTY LINE	WM	WATER METER
- - - - -	EXISTING EASEMENT	□	DOWNSPOUT WITH SPLASH BLOCK
---	STORM DRAIN PIPE	⊙	SANITARY SEWER MANHOLE
SS	4" SANITARY SEWER PIPE	•	SANITARY SEWER CLEANOUT
W	DOMESTIC WATER LINE	⊕	WATER VALVE
G	GAS LINE		
JT	JOINT TRENCH		
SD	EX STORM DRAIN MAIN		
SS	EX SANITARY SEWER MAIN		
W	EX WATER MAIN		
EM	ELECTRICAL METER		

ABBREVIATIONS:

BS = BOTTOM OF STEP	FL = FLOW LINE	R.O.W. = RIGHT-OF-WAY
BOW = BACK OF WALK	G = GARAGE	S = SLOPE
BW = BOTTOM OF WALL	GB = GRADE BREAK	SD = STORM DRAIN
C = CONCRETE	IE = INVERT ELEVATION	SR = STRAW ROLL
DWY = DRIVEWAY	L = LAWN	TC = TOP OF CURB
EG = EXISTING GRADE	LF = LINEAL FOOT	TC = TOP OF GRADE
EX = EXISTING	LP = LOW POINT	TP = TOP OF PAVEMENT
EP = EDGE OF PAVEMENT	N = NEW	TS = TOP OF STEP
FF = FINISHED FLOOR	P = PATIO OR PORCH	TW = TOP OF WALL
FG = FINISHED GRADE	PG = PERGOLA	TYP = TYPICAL

GRADING NOTES

- NEW SEWER LATERAL CONNECTION TO EXISTING SANITARY SEWER MAIN. (WORKS WITHIN RIGHT-OF-WAY REQUIRES A SEPARATE ENCROACHMENT PERMIT)
- INSTALL SANITARY SEWER CLEANOUT WITHIN 5' OF PROPERTY LINE PER WEST VALLEY SANITATION DISTRICT STANDARD DRAWING #3
- PROVIDE NEW SANITARY SEWER LATERAL FROM PROPERTY LINE TO BUILDING @ 2% SLOPE MINIMUM.
- SANITARY SEWER SERVICE ENTRY TO BUILDING. SEE ARCH PLANS FOR EXACT LOCATION AND LINE CONTINUATION TO BUILDING. INSTALL SANITARY SEWER CLEANOUT AT 2' OUTSIDE OF BUILDING
- NEW WATER SERVICE LINE CONNECTION TO EXISTING WATER MAIN. (WORKS WITHIN RIGHT-OF-WAY REQUIRES A SEPARATE ENCROACHMENT PERMIT)
- INSTALL NEW WATER METER PER CITY STANDARD
- NEW WATER SERVICE ENTRY. INSTALL INDIVIDUAL WATER AT 2' OUTSIDE OF BUILDING
- CONNECTION TO EXISTING UTILITY POLE. CONTRACTOR SHALL COORDINATE WITH PG&E PRIOR TO ANY CONSTRUCTION
- REMOVE EXISTING OVERHEAD ELECTRICAL, TELECOMMUNICATION AND CABLE TV SERVICE LINE AND INSTALL NEW UNDERGROUND JOINT TRENCH (ELECTRICAL, TELECOMMUNICATION AND CABLE TV) LINE TO BUILDING. COORDINATE WITH PG&E FOR LINE RELOCATION.
- NEW ELECTRICAL METER AND ELECTRICAL SERVICE ENTRY TO BUILDING. SEE ARCH PLANS FOR EXACT LOCATION

REV.	DATE	DESCRIPTION

UTILITY PLAN
401 DALLAS DR
CAMPBELL, CA 95008

SCALE


VERTICAL: 1"= AS SHOWN
HORIZONTAL: 1"= AS SHOWN

DATE: 09/30/2023
DESIGNED: HCL
DRAWN: BL
REVIEWED: HCL
JOB NO.: 20230039

Construction Best Management Practices (BMPs)

Construction projects are required to implement year-round stormwater BMPs.

Materials & Waste Management



Non-Hazardous Materials

- Berm and cover stockpiles of sand, dirt or other construction material with tarps when rain is forecast or when they are not in use.
- Use (but don't overuse) reclaimed water for dust control.
- Ensure dust control water doesn't leave site or discharge to storm drains.

Hazardous Materials

- Label all hazardous materials and hazardous wastes (such as pesticides, paints, thinners, solvents, fuel, oil, and antifreeze) in accordance with City, County, State and Federal regulations.
- Store hazardous materials and wastes in water tight containers, store in appropriate secondary containment, and cover them at the end of every work day or during wet weather or when rain is forecast.
- Follow manufacturer's application instructions for hazardous materials and do not use more than necessary. Do not apply chemicals outdoors when rain is forecast within 24 hours.
- Arrange for appropriate disposal of all hazardous wastes.

Waste Management

- Cover and maintain dumpsters. Check frequently for leaks. Place dumpsters under roofs or cover with tarps or plastic sheeting secured around the outside of the dumpster. A plastic liner is recommended to prevent leaks. Never clean out a dumpster by hosing it down on the construction site.
- Place portable toilets away from storm drains. Make sure they are in good working order. Check frequently for leaks.
- Dispose of all wastes and demolition debris properly. Recycle materials and wastes that can be recycled, including solvents, water-based paints, vehicle fluids, broken asphalt and concrete, wood, and cleared vegetation.
- Dispose of liquid residues from paints, thinners, solvents, glues, and cleaning fluids as hazardous waste.
- Keep site free of litter (e.g. lunch items, cigarette butts).
- Prevent litter from uncovered loads by covering loads that are being transported to and from site.

Construction Entrances and Perimeter

- Establish and maintain effective perimeter controls and stabilize all construction entrances and exits to sufficiently control erosion and sediment discharges from site and tracking off site.
- Sweep or vacuum any street tracking immediately and secure sediment source to prevent further tracking. Never hose down streets to clean up tracking.

Equipment Management & Spill Control




Maintenance and Parking

- Designate an area of the construction site, well away from streams or storm drain inlets and fitted with appropriate BMPs, for auto and equipment parking, and storage.
- Perform major maintenance, repair jobs, and vehicle and equipment washing off site.
- If refueling or vehicle maintenance must be done onsite, work in a bermed area away from storm drains and over a drip pan or drop cloths big enough to collect fluids. Recycle or dispose of fluids as hazardous waste.
- If vehicle or equipment cleaning must be done onsite, clean with water only in a bermed area that will not allow rinse water to run into gutters, streets, storm drains, or surface waters.
- Do not clean vehicle or equipment onsite using soaps, solvents, degreasers, or steam cleaning equipment, and do not use diesel oil to lubricate equipment or parts onsite.

Spill Prevention and Control

- Keep spill cleanup materials (e.g., rags, absorbents and cat litter) available at the construction site at all times.
- Maintain all vehicles and heavy equipment. Inspect frequently for and repair leaks. Use drip pans to catch leaks until repairs are made.
- Clean up leaks, drips and other spills immediately and dispose of cleanup materials properly.
- Use dry cleanup methods whenever possible (absorbent materials, cat litter and/or rags).
- Sweep up spilled dry materials immediately. Never attempt to "wash them away" with water, or bury them.
- Clean up spills on dirt areas by digging up and properly disposing of contaminated soil.
- Report significant spills to the appropriate local spill response agencies immediately. If the spill poses a significant hazard to human health and safety, property or the environment, you must report it to the State Office of Emergency Services. (800) 852-7550 (24 hours).

Earthmoving



Grading and Earthwork

- Schedule grading and excavation work during dry weather.
- Stabilize all denuded areas, install and maintain temporary erosion controls (such as erosion control fabric or bonded fiber matrix) until vegetation is established.
- Remove existing vegetation only when absolutely necessary, plant temporary vegetation for erosion control on slopes or where construction is not immediately planned.
- Prevent sediment from migrating offsite and protect storm drain inlets, drainage courses and streams by installing and maintaining appropriate BMPs (i.e. silt fences, gravel bags, fiber rolls, temporary swales, etc.).
- Keep excavated soil on site and transfer it to dump trucks on site, not in the streets.

Contaminated Soils

- If any of the following conditions are observed, test for contamination and contact the Regional Water Quality Control Board:
 - Unusual soil conditions, discoloration, or odor.
 - Abandoned underground tanks.
 - Abandoned wells
 - Buried barrels, debris, or trash.
- If the above conditions are observed, document any signs of potential contamination and clearly mark them so they are not disturbed by construction activities.

Landscaping

- Protect stockpiled landscaping materials from wind and rain by storing them under tarps all year-round.
- Stack bagged material on pallets and under cover.
- Discontinue application of any erodible landscape material within 2 days before a forecast rain event or during wet weather.

Concrete Management and Dewatering



Concrete Management

- Store both dry and wet materials under cover, protected from rainfall and runoff and away from storm drains or waterways. Store materials off the ground, on pallets. Protect dry materials from wind.
- Wash down exposed aggregate concrete only when the wash water can (1) flow onto a dirt area; (2) drain onto a bermed surface from which it can be pumped and disposed of properly; or (3) block any storm drain inlets and vacuum washwater from the gutter. If possible, sweep first.
- Wash out concrete equipment/trucks offsite or in a designated washout area onsite, where the water will flow into a temporary waste pit, and make sure wash water does not leach into the underlying soil. (See CASQA Construction BMP Handbook for properly designed concrete washouts.)

Dewatering

- Discharges of groundwater or captured runoff from dewatering operations must be properly managed and disposed. When possible, send dewatering discharge to landscaped area or sanitary sewer. If discharging to the sanitary sewer, call your local wastewater treatment plant.
- Divert run-on water from offsite away from all disturbed areas.
- When dewatering, notify and obtain approval from the local municipality before discharging water to a street gutter or storm drain. Filtration or diversion through a basin, tank, or sediment trap may be required.
- In areas of known or suspected contamination, call your local agency to determine whether the ground water must be tested. Pumped groundwater may need to be collected and hauled off-site for treatment and proper disposal.

Paving/Asphalt Work



Paving

- Avoid paving and seal coating in wet weather or when rain is forecast, to prevent materials that have not cured from contacting stormwater runoff.
- Cover storm drain inlets and manholes when applying seal coat, slurry seal, fog seal, or similar materials.
- Collect and recycle or properly dispose of excess abrasive gravel or sand. Do NOT sweep or wash it into gutters.

Sawcutting & Asphalt/Concrete Removal

- Protect storm drain inlets during saw cutting.
- If saw cut slurry enters a catch basin, clean it up immediately.
- Shovel or vacuum saw cut slurry deposits and remove from the site. When making saw cuts, use as little water as possible. Sweep up, and properly dispose of all residues.




Santa Clara Valley

Urban Runoff

Pollution Prevention Program

Painting & Paint Removal



Painting Cleanup and Removal

- Never clean brushes or rinse paint containers into a street, gutter, storm drain, or stream.
- For water-based paints, paint out brushes to the extent possible, and rinse into a drain that goes to the sanitary sewer. Never pour paint down a storm drain.
- For oil-based paints, paint out brushes to the extent possible and clean with thinner or solvent in a proper container. Filter and reuse thinners and solvents. Dispose of excess liquids as hazardous waste.
- Sweep up or collect paint chips and dust from non-hazardous dry stripping and sand blasting into plastic drop cloths and dispose of as trash.
- Chemical paint stripping residue and chips and dust from marine paints or paints containing lead, mercury, or tributyltin must be disposed of as hazardous waste. Lead based paint removal requires a state-certified contractor.

DESCRIPTION

DATE

REV.

BLUEPRINT FOR A CLEAN BAY

401 DALLAS DR
CAMPBELL, CA 95008



GREEN
CIVIL ENGINEERING, INC.
INFO@GREEN-CE.COM
1900 S. NORFOLK ST. SUITE #350
SAN MATEO, CA 94403



SCALE

VERTICAL: 1"= AS SHOWN
HORIZONTAL: 1"= AS SHOWN

DATE: 09/30/2023

DESIGNED: HCL

DRAWN: BL

REVIEWED: HCL

JOB NO.: 20230039

SHEET

C4

4 OF 4 SHEETS

Storm drain polluters may be liable for fines of up to \$10,000 per day!

PLANT LEGEND AND NOTES

Symbol	Species	Size	Water	WUCOLS
	Sod lawn 100% dwarf fescue	high	.7	
	Anigozanthos white/ Kangaroo Paw @ 36" oc	1 gallon low	3	
	Lomandra Baby Breeze @ 36" oc	1 gallon low	3	
	Lomandra dwarf variegated @ 36" oc	1 gallon low	3	
A	Olea Little Olive/ Dwarf Olive	5 gallon low	3	
B	Loropetalum Jazz Hands white	5 gallon low	3	
C	Cotinus Royal Purple/ Smoke Tree	15 gallon low	3	
D	Prunus carolina Compacta/ Carolina Laurel	15 gallon low	3	
E	Perovskia atriplicifolia Blue Spires	5 gallon low	3	
F	Sarcococca ruscifolia	5 gallon low	3	
T1	Olea europaea Swan Hill multi trunk/ Fruitless Olive	24" box low	3	

- 1) Thoroughly prepare soil prior to planting. Break up hardpan and till prior to adding amendments.
- 2) Incorporate 4 cu of compost per 1000 sf, 6" into native soil.
- 3) Verify placement of all plant material prior to planting.
- 4) Verify location of all underground utilities prior to construction.
- 5) Spread 3" of wood chip (Prochip Brown Tone, or equal) mulch after planting. Verify color with Owner. Mulch to be placed around all new and existing planting as well as in side yard areas when no planting is proposed.
- 6) Save and repurpose existing cobbles at front yard.




ANIGOZANTHOS LOMANDRA LOMANDRA



OLEA LOROPETALUM COTINUS PRUNUS



SARCOCOCCA PEROVSKIA OLEA



MAGNOLIA TREE TO REMAIN
REPURPOSE AND RESET EXISTING COBBLES

DALLAS DRIVE



MASTER PLANTING PLAN

1/8" = 1'-0"

W. Jeffrey Heid
Landscape Architect
C-2235

1465 Winzer Place
Gilroy, Ca. 95020
tel 408 691-5207
email wjheidasia@gmail.com

OWNERSHIP AND USE OF DRAWINGS
All drawings, specifications and copies thereof furnished by W. Jeffrey Heid Landscape Architect are and shall remain its property. They are to be used only with respect to this Project and are not to be used on any other project. Submission or distribution to meet official regulatory requirements or for other purposes in connection with the Project is not to be construed as publication in derogation of W. Jeffrey Heid Landscape Architect, common law, copyright or other reserved rights.

REVISED 1/30/24
REVISED 2/6/24



BARAJAS
RESIDENCE

for:
ALFREDO BARAJAS
401 DALLAS DRIVE
CAMPELL, CA. 95008

MASTER PLANTING
PLAN

date: 1/11/24
scale: NOTED
drawn by: WJH
job no. 202401
sheet



of shts

IRRIGATION LEGEND



Rachio 3 weatherbased controller located in garage - verify electrical - run control valve wires from controller outside to irrigation mainline within schedule 80 pvc conduit.



Febco # 765-1" pressure vacuum breaker

1" schedule 40 pvc mainline - min. depth 18"



Rainbird PEB series control valves with AVB, in line pressure reducer set to 35 psi and Y filter for drip circuits and without for lawn

Schedule 40 pvc lateral lines - min. depth 12"



Rainbird Xeribuq 1 gph pressure compensating emitters set on 1/2" drip line (2 emitters to each 1 gallon plan, 3 to each 5 gallon and 4 for larger) locate on opposite sides of rootball and install flush end valve at the end of each drip line run

Hunter MP Rotator on 6" pop up for lawn area - verify nozzle selection in field

Rainbird #140I bubbler for trees and large shrubs (2 per tree at opposite sides)


Control valve number

- Circuit #1 - drip/5 gpm
- Circuit #2 - spray/3 gpm
- Circuit #3 - drip/7 gpm
- Circuit #4 - drip/3 gpm
- Circuit #5 - spray/12 gpm
- Circuit #6 - drip/10 gpm
- Circuit #7 - bubbler/2 gpm
- Circuit #8 - drip/3 gpm

- 1) Verify water source and placement of backflow preventer - cover with lockable weather blanket.
- 2) Verify operation of system before backfilling trenches. Drip line to be secured to grade with stakes and covered with final mulch.
- 3) System layout is diagrammatic, actual field conditions will dictate final layout, addition of drip line, etc.
- 4) Verify location of all underground utilities prior to any trenching or excavation.
- 5) Contractor shall provide all necessary safety precautions throughout construction.
- 6) Contractor to set irrigation schedule based on time of year, weather, plant need and to eliminate runoff and water waste.


- 1) "I have complied with the criteria of the ordinance and applied them for the efficient use of water in the landscape design plans".
- 2) "A diagram of the irrigation plan showing hydrozones shall be kept with the irrigation controller for subsequent management purposes."
- 3) "A Certificate of Completion shall be filled out and certified by either the designer of the landscape plans, irrigation plans, or the licensed landscape contractor for the project".
- 4) "An irrigation audit report shall be completed at the time of final inspection."
- 5) "Pressure regulating devices are required if water pressure is below or exceeds the recommended pressure of the specified irrigation devices."
- 6) Manual shut-off valves shall be required, as close as possible to the point of connection of the water supply, to minimize water loss in case of an emergency or routine repair.
- 7) "Check valves or anti-drain valves are required on all sprinkler heads where low point drainage could occur."

- 1 SINGLE-OUTLET BARB INLET X BARB OUTLET EMITTER:
RAIN BIRD XERI-BUG EMITTER
- 2 5/8" POLYETHYLENE TUBING:
RAIN BIRD XF SERIES TUBING OR
RAIN BIRD XT-700 XERI-TUBE OR
RAIN BIRD XBS BLACK STRIPE TUBING
- 3 FINISH GRADE



- NOTES:
1. USE RAIN BIRD XERIMAN TOOL XM--TOOL TO INSERT EMITTER DIRECTLY INTO 1/2" POLYETHYLENE TUBING.
 2. RAIN BIRD XERI-BUG BARB X BARB EMITTERS ARE AVAILABLE IN THE FOLLOWING MODELS:
XB-05PC 0.5 GPH XB-10PC 1.0 GPH XB-20PC 2.0 GPH


A XERI-BUG INTO 1/2-INCH TUBING
N.T.S. OPTION 1 1-14-10




- 1 SINGLE-OUTLET BARB INLET X BARB OUTLET EMITTER:
RAIN BIRD XERI-BUG EMITTER
- 2 UNIVERSAL 1/2" TUBING STAKE:
RAIN BIRD TS-025
- 3 1/4" DISTRIBUTION TUBING:
RAIN BIRD XQ TUBING
(LENGTH AS REQUIRED)
- 4 TOP OF MULCH
- 5 1/4" SELF-PIERCING BARB CONNECTOR:
RAIN BIRD SPB-025
- 6 1/2" POLYETHYLENE TUBING:
RAIN BIRD XF SERIES TUBING OR
RAIN BIRD XT-700 XERI-TUBE OR
RAIN BIRD XBS BLACK STRIPE TUBING
- 7 FINISH GRADE

- NOTES:
1. USE RAIN BIRD XERIMAN TOOL XM--TOOL TO INSERT BARB CONNECTOR DIRECTLY INTO 1/2" POLYETHYLENE TUBING.
 2. SHOULD THE EMITTER BECOME DISLODGED UNREGULATED FLOW WILL OCCUR.
 3. RAIN BIRD XERI-BUG BARB X BARB EMITTERS ARE AVAILABLE IN THE FOLLOWING MODELS:
XB-05PC 0.5 GPH XB-10PC 1.0 GPH XB-20PC 2.0 GPH

B BARB CONNECTOR INTO 1/2" TUBING, STAKE AND XERI-BUG
N.T.S. OPTION 3 1-18-10




C CONTROL VALVE DETAIL



- 1 PRESSURE COMPENSATING FULL-CIRCLE BUBBLER:
RAIN BIRD 1400
- 2 KBI FLEX RISER
- 3 FINISH GRADE/TOP OF MULCH
- 4 SCHEDULE 80 RISER
(LENGTH AS REQUIRED)
- 5 2 1/2" MARLEX FITTINGS TO CREATE SWING JOINT
- 6 SCHEDULE 40 PVC LATERAL PIPE
- 7 PVC SCH 40 TEE OR ELL

D PRESSURE COMPENSATING FULL-CIRCLE BUBBLER 1400 SERIES ON RISER
N.T.S. 1400 SERIES ON RISER



DALLAS DRIVE



IRRIGATION PLAN

1/8" = 1'-0"

W. Jeffrey Heid
Landscape Architect
C-2235

1465 Winzer Place
Gilroy, Ca. 95020
tel 408 691-5207
email wheidasia@gmail.com

OWNERSHIP AND USE OF DRAWINGS
All drawings, specifications and copies thereof furnished by W. Jeffrey Heid Landscape Architect are and shall remain its property. They are to be used only with respect to this Project and are not to be used on any other project. Submission or distribution to meet official regulatory requirements or for other purposes in connection with the Project is not to be construed as publication in derogation of W. Jeffrey Heid Landscape Architect, common law, copyright or other reserved rights.



BARAJAS
RESIDENCE

for:
ALFREDO BARAJAS
401 DALLAS DRIVE
CAMPBELL, CA. 95008

IRRIGATION PLAN

date: 2/6/24
scale: NOTED
drawn by: WJH
job no. 202401
sheet

L 3

of shts



Anaheim Office
February 5, 2024
Report# 24-031-0017

W. Jeffrey Heid Landscape
6179 Oneida Drive
Santa Jose, CA 95123

Attn: Jeff

RE: Barajas - Campbell, CA

Background

A soil sample was received on January 31, 2024 identified as site soil taken from a depth of 6-9 inches from areas where new landscaping is scheduled for installation. Fertilizer and amendment recommendations were requested. The sample was analyzed for horticultural suitability, fertility and physical characteristics. The results of the analyses are attached.

Analytical Results and Comments

The reaction of the sample is slightly acidic (pH 6.8) with qualitative lime absent. These levels are within the range preferred for most plants and no pH adjustment is suggested.

Salinity (Ece), sodium and boron are all safely low. The sodium adsorption ratio (SAR) shows sodium is adequately balanced by soluble calcium and magnesium; this balance is important for soil structure quality, which relates to the rate at which water infiltrates the soil.

According to the USDA Soil Classification, the less than 2mm fraction of this sample is classified as sandy clay loam. The 23.1% gravel present classifies this material as gravelly. This, in combination with a relatively wide distribution of particle sizes in the sand category, indicates that the soil at this site may have some tendency to compact. Organic content is moderate at 2.32% dry weight. Based on this information, the estimated infiltration rate is also moderate at 0.25 inch per hour. Infiltration rates may vary due to differences in compaction across the site.

In terms of fertility, nitrogen and calcium are low. Phosphorus is low optimum. Magnesium is high optimum. In the minor element group, copper is high optimum and manganese is low. The remaining nutrients are in sufficient supply.

Recommendations

Incorporation of nitrogen, phosphorus, calcium and sulfur fertilizers is recommended at the time of planting. Incorporation of a nitrogen stabilized organic amendment or composted greenwaste product is recommended in order to improve soil nutrient holding capacity and porosity. If a composted greenwaste amendment is chosen, that would provide additional phosphorus and potassium as well as supplemental micronutrients, product depending.

The primary symptom of manganese deficiencies is a general yellowing of leaves with veins remaining green. Manganese deficiency symptoms appear first on younger leaves. If these symptoms are present after plant installation they may be treated with an application of a chelated micronutrient product at the manufacturer's recommended rate. Incorporation of a composted greenwaste amendment would also provide additional micronutrients and may be sufficient to negate any deficiency, product depending.

To Prepare for Mass Planting:

Drainage of the root zone should be improved by first loosening the top 10 inches of any undisturbed or compacted soil. The following materials should then be evenly spread and thoroughly blended with the top 6 inches of soil to form a homogeneous layer:

Amount per 1000 Square Feet	
4 cubic yards	Nitrogen Stabilized Organic Amendment*
9 pounds	16-20-0* Ammonium Phosphate
50 pounds	Gypsum

For all turf areas the organic amendment should be decreased by half.

*The rate may change based on the analysis of the chosen organic amendment. This rate is based on 270 lbs. of dry weight of organic matter per cubic yard of amendment.

To Prepare Backfill for Trees and Shrubs:

- Excavate planting pits at least twice as wide as the diameter of the rootball.
- Soil immediately below the rootball should be left undisturbed to provide support but the sides and the bottom around the side should be cultivated to improve porosity.
- The top of the rootball should be at or slightly above final grade.
- The top 12 inches of backfill around the sides of the rootball of trees and shrubs may consist of the above amended soil or may be prepared as follows:

4 parts	Site Soil
1 part	Nitrogen Stabilized Organic Amendment*

Uniformly blended with:

Amount / Cubic Yard of Backfill	
1/2 pound	16-20-0* Ammonium Phosphate
2 1/2 pounds	Gypsum

- Backfill below 12 inches required for 24-inch box or larger material should not contain the organic amendment or fertilizers.
- Ideally a weed and turf free zone should be maintained just beyond the diameter of the planting hole. A 2-4 inch deep layer of coarse mulch can be placed around the tree or shrub. Mulch should be kept a minimum 4 inches from the trunk.
- Irrigation of new plantings should take into consideration the differing texture of the rootball substrate and surrounding soil matrix to maintain adequate moisture during this critical period of establishment.

Maintenance

Maintenance fertilization should rely primarily on a nitrogen only program supplemented with a complete fertilizer in the fall and spring. Beginning 45 days after installation, calcium nitrate (15-5-0-0) should be applied at a rate of 7 pounds per 1000 square feet with reapplication every 45-60 days. Alternatively, slow

release Sulfur Coated Urea (43-0-0) may be applied at 6 pounds per 1000 square feet every 90 days. Keep in mind that long term use of sulfur coated urea can adjust the pH downward and this is something to monitor for. Once plants are performing satisfactorily, the frequency of fertilization may be decreased depending on color and rate of growth desired. Early fall and spring, substitute a complete fertilizer such as 16-8-8 to help insure continuing adequate phosphorus and potassium.

Alternatively, Blood Meal (12-0-0) provides available nitrogen fairly rapidly while materials such as Feather Meal (12-0-0), Soybean or Cotton Seed Meal (7-1-1) are slower to provide available nitrogen, but they extend the length of time they make this contribution. In order to provide a good supply of nitrogen for a 3-4 month time frame a good combination would be 6 pounds Blood Meal and 14 pounds Feather Meal per 1000 square feet. In the fall and spring, substitute a complete organic fertilizer such as 5-5-5 applied at the manufacturer's label rate. Or in general planting areas, nutrient rich composted greenwaste may be spread in a 1 to 2 inch layer, which generally carries enough nutrition to boost complete nutrition though a source of nitrogen might also be added at a half rate to assure adequate nitrogen availability.

If we can be of any further assistance, please feel free to contact us.

Joe Kiefer, CCA

kiefer@waypointanalytical.com

4741 East Hunter Ave., Ste. A Anaheim CA 92807

(714) 282-8777 (714) 282-8575 fax

www.waypointanalytical.com

Page 3 of 4

Project: Barajas - Campbell, CA Report No: 24-031-0017
Purchase Order: Date Recd: 01-01-2024
Date Printed: 02/05/2024 Page: 1 of 1

Sample Description - Sample ID	Half Set %	pH	EC	Clay %	NO ₃ -N ppm	NH ₄ -N ppm	PO ₄ -P ppm	K ppm	Ca ppm	Mg ppm	Cu ppm	Zn ppm	Mn ppm	Fe ppm	Organic % (dry wt)	Lab. No.																																												
																	TEC	SO ₄ -S ppm	Boron ppm	Copper ppm	Manganese ppm	Sulfur ppm																																						
Site Soil	18	6.8	0.16	1	12	72	101	206	100	5.6	0.8	2	26	3.30	0.30	04027																																												
<table border="1"> <thead> <tr> <th colspan="4">Saturation Extract Values</th> <th colspan="4">Gravel %</th> <th colspan="4">Percent of Sample Passing 2 mm Screen</th> <th rowspan="2">USDA Soil Classification</th> <th rowspan="2">Lab. No.</th> </tr> <tr> <th>Ca</th> <th>Mg</th> <th>Na</th> <th>K</th> <th>B</th> <th>SO₄</th> <th>SAR</th> <th>Coarse 3-12</th> <th>Fine 2-1</th> <th>Very Coarse 1-2</th> <th>Coarse 0.8-1</th> <th>Med to Very Fine 0.6-0.5</th> <th>Silt 0.075-0.05</th> <th>Clay 0-0.075</th> </tr> </thead> <tbody> <tr> <td>8.2</td> <td>1.48</td> <td>3.07</td> <td>8.58</td> <td>0.26</td> <td>1.2</td> <td>2.1</td> <td>11.2</td> <td>0.8</td> <td>4.8</td> <td>4.8</td> <td>46</td> <td>37.9</td> <td>25.2</td> <td>Clayey Sandy Clay Loam</td> <td>04027</td> </tr> </tbody> </table>																	Saturation Extract Values				Gravel %				Percent of Sample Passing 2 mm Screen				USDA Soil Classification	Lab. No.	Ca	Mg	Na	K	B	SO ₄	SAR	Coarse 3-12	Fine 2-1	Very Coarse 1-2	Coarse 0.8-1	Med to Very Fine 0.6-0.5	Silt 0.075-0.05	Clay 0-0.075	8.2	1.48	3.07	8.58	0.26	1.2	2.1	11.2	0.8	4.8	4.8	46	37.9	25.2	Clayey Sandy Clay Loam	04027
Saturation Extract Values				Gravel %				Percent of Sample Passing 2 mm Screen				USDA Soil Classification	Lab. No.																																															
Ca	Mg	Na	K	B	SO ₄	SAR	Coarse 3-12	Fine 2-1	Very Coarse 1-2	Coarse 0.8-1	Med to Very Fine 0.6-0.5			Silt 0.075-0.05	Clay 0-0.075																																													
8.2	1.48	3.07	8.58	0.26	1.2	2.1	11.2	0.8	4.8	4.8	46	37.9	25.2	Clayey Sandy Clay Loam	04027																																													

Sulfuric Acid (1:50 dilution) for nitrate-nitrogen; Murexide for nitrate-nitrogen; Nessler for ammonia-nitrogen; Ascorbic Acid for nitrite-nitrogen; Phosphomolybdate for phosphate-phosphorus; Inductively Coupled Plasma Atomic Emission Spectroscopy for calcium, magnesium, potassium, sodium, copper, zinc, manganese, iron, boron, selenium, and sulfur. Organic carbon determined by loss on ignition. All values are in mg/kg unless otherwise specified. Page 4 of 4

SOIL MANAGEMENT REPORT

- Due to the amount of pavement or soil coverage, scraping and salvaging any topsoil is limited to no value.
- Instead, once the site is cleared of pavement and new construction is near completion, all planted areas should be broken up and tilled thoroughly to break up the existing and created hardpan during construction operation.
- During the process of breaking up and amending the soil for new planting, the site specific soil preparation specifications from Waypoint Analytical shall be followed to improve soil texture and nutrient levels.

W. Jeffrey Heid
Landscape Architect
C-2235

1465 Winzer Place
Gilroy, Ca. 95020
tel 408 691-5207
email whjeid@comcast.net

OWNERSHIP AND USE OF DRAWINGS

All drawings, specifications and copies thereof furnished by W. Jeffrey Heid Landscape Architect are and shall remain its property. They are to be used only with respect to this Project and are not to be used on any other project. Submission or distribution to meet official regulatory requirements or for other purposes in connection with the Project is not to be construed as publication in derogation of W. Jeffrey Heid Landscape Architect's common law, copyright or other reserved rights.



BARAJAS
RESIDENCE

for:
ALFREDO BARAJAS
401 DALLAS DRIVE
CAMPBELL, CA. 95008

SOIL MANAGEMENT PLAN

date: 2/6/24
scale: NOTED
drawn by: W.J.H.
job no. 202401
sheet L 4
of 8 sheets



JOSHUA LIU & KEVIN YU, PROJECT DESIGNERS
 ARCHITECTS
 1500 S. GARDEN ST., SUITE 100
 CAMPBELL, CA 95008
 (408) 351-1225
 JOSHUALIU@GKWARCHITECTS.COM

GORDON K WONG, ARCHITECT LIC# 34045
 ARCHITECT
 1500 S. GARDEN ST., SUITE 100
 CAMPBELL, CA 95008
 (408) 351-1225
 GORDONKWONG@GKWARCHITECTS.COM



NEW SINGLE FAMILY RESIDENCE
 4071 DALLAS DRIVE
 CAMPBELL, CA 95008

Architectural, Roof Plan, Proposed


Revision	Description

Architectural, Roof Plan, Proposed

A101

SCALE AS INDICATED

2/7/2024 10:37:54 AM



- ROOF PLAN, KEYNOTES, PROPOSED**
- 1 SKYLIGHT, SEE SHEET A600 FOR DETAILS
 - 2 FASCIA, SEE SHEET A200 & A600 FOR DETAILS
 - 3 GUTTERS AND DOWNSPOUTS GSM PAINTED
 - 4 STANDING SEAM METAL ROOF, PAC-150 180 DEGREE, SEE SHEET A600 FOR DETAILS
 - 5 RIDGE VENT
 - 6 STEEL ATTIC VENT
 - 7 VELLUX SKYLIGHT
 - 8 BUILDING OUTLINE
 - 9 SOLAR PANEL, TYP.

- ROOF PLAN, LEGEND, PROPOSED**
- D DORMER VENT, 12" X 24"
 - DS DOWNSPOUT
 - EAVE VENT, 5.5' X 22.5'
 - RIDGE VENT
 - - - - BUILDING FOOTPRINT

CALIFORNIA ENERGY CODE 150.1, C.14 PHOTOVOLTAIC REQUIREMENTS

$$KW = (CFA \times A) \times 1000 + (NDWELL \times B)$$

$$= (3,591 \text{ SF} \times 0.586) \times 1,000 + (1 \times 1.21)$$

$$= 2.10 + 1.21$$

KW = 3.31 => REQUIRED SYSTEM SIZING

ABBREVIATIONS

- KW = KWDC SIZE OF PV SYSTEM
- CFA= CONDITIONED FLOOR AREA = 3,591 SF
- NDWELL= NUMBER OF DWELLING UNITS = 1
- A= ADJUSTMENT FACTOR, CLIMATE ZONE 4 = 0.586
- B= DWELLING ADJUSTMENT FACTOR, CLIMATE ZONE 4 = 1.21

PER CRC R906.2 - ROOF VENTILATION REQUIREMENTS


THE MINIMUM NET FREE VENTILATION AREA SHALL BE 1/150 OF THE AREA OF THE VENTED SPACE

(P) TOTAL 1ST FLOOR ATTIC AREA =	- SF
(A) ATTIC AREA =	- SF
REQUIRED: (- SF / 150) X 144 =	- SQ IN
(A) HALF OF AREA ALLOCATED TO DORMER & RIDGE VENT (EXHAUST):	- SQ IN
(P) RIDGE VENT:	10.96 SQ IN, NFV PER LINEAR FOOT
CALCS TBD	
(A) HALF OF AREA ALLOCATED TO EAVE VENT (INTAKE):	- SQ IN
(P) EAVE VENT:	28 SQ IN, NFV
CALCS TBD	
(B) ATTIC AREA =	- SF
REQUIRED: (- SF / 150) X 144 =	- SQ IN
(B) HALF OF AREA ALLOCATED TO DORMER & RIDGE VENT (EXHAUST):	- SQ IN
(P) RIDGE VENT:	10.96 SQ IN, NFV PER LINEAR FOOT
CALCS TBD	
(B) HALF OF AREA ALLOCATED TO EAVE VENT (INTAKE):	- SQ IN
(P) EAVE VENT:	28 SQ IN, NFV
CALCS TBD	
(P) TOTAL 2ND FLOOR ATTIC AREA =	- SF
(C) ATTIC AREA =	- SF
REQUIRED: (- SF / 150) X 144 =	- SQ IN
(C) HALF OF AREA ALLOCATED TO DORMER & RIDGE VENT (EXHAUST):	- SQ IN
(P) RIDGE VENT:	10.96 SQ IN, NFV PER LINEAR FOOT
CALCS TBD	
(C) HALF OF AREA ALLOCATED TO EAVE VENT (INTAKE):	- SQ IN
(P) EAVE VENT:	28 SQ IN, NFV
CALCS TBD	

ROOF DRAINAGE CALCULATION

PER CPC TABLE 1103.1

ROOF AREA:	
LEVEL 1:	- SF
LEVEL 2:	- SF
HOURLY RATE: 1.5 IN PER PIPE SIZE 2":	1,920 SF
LEVEL 1:	- SF / 1,920 SF =
	- PIPES (REQUIRED)
LEVEL 2:	- SF / 1,920 SF =
	- PIPE (REQUIRED)
TOTAL DOWNSPOUTS:	- PIPES (PROVIDED)





JOSHUALIU & KEVIN YU, PROJECT DESIGNERS
 ARCHITECTS
 1500 CALIFORNIA STREET, SUITE 100
 CAMPBELL, CA 95008
 JOSHUALIU@GKWMARCHITECTS.COM

GORDON K WONG, ARCHITECT LICI 34045
 ARCHITECT
 1500 CALIFORNIA STREET, SUITE 100
 CAMPBELL, CA 95008
 GORDONKWONG@GKWMARCHITECTS.COM



Architectural, Area Diagrams

NEW SINGLE FAMILY RESIDENCE
 401 DALLAS DRIVE
 CAMPBELL, CA 95008


Revision Schedule

Architectural, Area Diagrams

A102

SCALE AS INDICATED

2/7/2024 10:37:59 AM




(P) 2ND FLOOR
 AREA: 1,268 SF
 COUNTABLE AREA

BUILDING AREA CALCULATION

(P) PRIMARY HOUSE	3,466 SF
- 1ST FLOOR	2,198 SF
- 2ND FLOOR	1,268 SF
(P) ATTACHED 2-CAR GARAGE	496 SF
(P) TOTAL RESIDENCE (COUNTABLE AREA)	3,962 SF
- FRONT PORCH	265 SF
- REAR PORCH	420 SF
(P) TOTAL PORCH AREA (NOT COUNTABLE AREA):	685 SF

2 2nd Floor, Area Diagram
 1/4" = 1'-0"




(P) REAR PORCH
 AREA: 420 SF
 NOT COUNTABLE AREA


(P) 1ST FLOOR
 AREA: 2,198 SF
 COUNTABLE AREA

(P) FRONT PORCH
 AREA: 265 SF
 NOT COUNTABLE AREA

(P) GARAGE
 AREA: 496 SF
 COUNTABLE AREA




1 1st Floor, Area Diagram
 1/4" = 1'-0"





1 Cross Section, AA
1/4" = 1'-0"



2 Cross Section, BB
1/4" = 1'-0"

SECTION, PROPOSED, KEYNOTES

- 1 STANDING SEAM METAL ROOF
- 2 CONCRETE SLAB
- 3 HEADER, SEE STRUCTURAL
- 4 RADIANT BARRIER ROOF SHEATHING
- 5 2X TYP. FASCIA BOARD PRE-PRIMED PAINTED
- 6 ENGINEERED BEAM, SEE STRUCTURAL
- 7 FIRE STOP
- 8 R-19 INSULATION @ RAISED FLOOR AREA
- 9 R-21 INSULATION @ PERIMETER WALLS
- 10 R-38 INSULATION @ CEILING
- 11 R-38 RIGID INSULATION, SPRAY FOAM @ VAULTED CEILING
- 12 SKYLIGHT
- 13 TYP. 24 GA. GALV. SHEET METAL GUTTER & DOWN SPOUT
- 14 ROOF PITCH TO MATCH / SYMMETRICAL
- 15 FOUNDATION, SEE STRUCTURAL
- 16 FLOOR JOISTS, SEE STRUCTURAL

GENERAL NOTES:

1. THE RISER HEIGHT SHALL BE NOT MORE THAN 7 3/4 INCHES. THE RISER SHALL BE MEASURED VERTICALLY BETWEEN LEADING EDGES OF THE ADJACENT TREADS. (CBC - R311.7.6.1)
2. THE TREAD DEPTH SHALL BE NOT LESS THAN 10 INCHES. THE TREAD DEPTH SHALL BE MEASURED HORIZONTALLY BETWEEN THE VERTICAL PLANES OF THE FOREMOST PROJECTION OF ADJACENT TREADS AND AT A RIGHT ANGLE TO THE TREADS LEADING EDGE. (CBC - R311.7.5.2)
3. HANDRAILS SHALL NOT BE LESS THAN 34" OR MORE THAN 38" IN HEIGHT ABOVE THE STAIR NOSING. HANDRAILS SHALL BE CONTINUOUS PER FLIGHT OF STAIRS. HANDRAILS SHALL BE 1-1/2" CLR. OF ALL ADJACENT FIN. MATLS AND ENDS SHALL RETURN TO OR TERMINATE IN NEWEL POSTS OR SAFE TERMINALS. HANDRAILS SHALL BE 1-1/4" IN CROSS-SECTIONAL DIMENSION OR APPROVED EQUAL AND BE SMOOTH WITH NO SHARP EDGES/COOR.
4. STAIR & RAILING SUPPLIER SHALL SATISFY ALL BUILDING DEPARTMENT APPROVAL REQUIREMENTS FOR THE PRODUCTS THEY PROVIDE OR INSTALL.
5. THE GUARDRAIL CONST. SHALL BE ABLE TO RESIST A LOAD OF 20 LBS PER LIN. FT. APPLIED HORIZONTALLY ALONG THE RAIL.
6. REQUIRED GUARDS SHALL NOT HAVE OPENINGS THAT ALLOW THE PASSAGE OF A SPHERE 4 INCHES IN DIAMETER FROM THE WALKING SURFACE REQUIRED GUARD HEIGHT. (CBC 1015.4)
7. FOR OCCUPANCIES IN GROUP R-3, WHERE TOP OF THE GUARD SERVES AS A HANDRAIL ON THE OPEN SIDES OF STAIRS, THE TOP OF THE GUARD SHALL NOT BE LESS THAN 34 INCHES AND NOT MORE THAN 38 INCHES MEASURED VERTICALLY FROM A LINE CONNECTING THE LEADING EDGES OF THE TREADS. (CBC 1015.3)
8. THE HANDRAIL CONSTRUCTION SHALL BE ABLE TO RESIST A LOAD OF 200 LBS APPLIED IN ANY DIRECTIONS AT ANY POINT ALONG THE TOP RAIL.
9. WHERE HANDRAILS ARE NOT CONTINUOUS BETWEEN FLIGHTS, THE HANDRAILS SHALL EXTEND HORIZONTALLY NOT LESS THAN 12 INCHES BEYOND THE TOP RISER AND CONTINUE TO SLOPE FOR THE DEPTH OF ONE TREAD BEYOND THE BOTTOM RISER. THE EXTENSIONS OF HANDRAILS SHALL BE IN THE SAME DIRECTION OF THE FLIGHTS OF STAIRS AT STAIRWAYS. (CBC 1014.6)
10. HANDRAIL GRASPABILITY (CBC 1014.3)
 - A. TYPE I- HANDRAILS WITH A CIRCULAR CROSS SECTION SHALL HAVE AN OUTSIDE DIAMETER OF NOT LESS THAN 1 1/4 INCHES (32 MM) AND NOT GREATER THAN 2 INCHES (51 MM), WHERE THE HANDRAIL IS NOT CIRCULAR, IT SHALL HAVE A PERIMETER DIMENSION OF NOT LESS THAN 4 INCHES (102 MM) AND NOT GREATER THAN 6 1/4 INCHES (160 MM) WITH A MAXIMUM CROSS-SECTIONAL DIMENSION OF 2 1/4 INCHES (57 MM) AND MINIMUM CROSS-SECTIONAL DIMENSION OF 1 INCH (25 MM). EDGES SHALL HAVE A MINIMUM RADIUS OF 0.01 INCH (0.25 MM).
 - B. TYPE II- HANDRAILS WITH A PERIMETER GREATER THAN 6 1/4 INCHES (160 MM) SHALL PROVIDE A GRASPABLE FINGER RECESS AREA ON BOTH SIDES OF THE PROFILE. THE FINGER RECESS SHALL BEGIN WITHIN A DISTANCE OF 3/4 INCH (19 MM) MEASURED VERTICALLY FROM THE TALLEST PORTION OF THE PROFILE AND ACHIEVE A DEPTH OF NOT LESS THAN 5/16 INCH (8 MM) WITHIN 7/8 INCH (22 MM) BELOW THE WIDEST PORTION OF THE PROFILE. THIS REQUIRED DEPTH SHALL CONTINUE FOR NOT LESS THAN 3/8 INCH (10 MM) TO A LEVEL THAT IS NOT LESS THAN 1/4 INCHES (6 MM) BELOW THE TALLEST PORTION OF THE PROFILE. THE WIDTH OF THE HANDRAIL ABOVE THE RECESS SHALL BE NOT LESS THAN 1 1/4 INCHES (32 MM) TO NOT GREATER THAN 2 3/4 INCHES (70 MM), EDGES SHALL HAVE A MINIMUM RADIUS OF 0.01 INCH (0.25 MM).



GORDON K WONG ARCHITECT LICI 34045
1500 S. GARDEN ST. SUITE 100
CAMPBELL, CA 95008
GORDONK.WONG@GKWARCHITECTS.COM

GORDON K WONG ARCHITECT LICI 34045
1500 S. GARDEN ST. SUITE 100
CAMPBELL, CA 95008
GORDONK.WONG@GKWARCHITECTS.COM



Architectural, Cross Sections, AA & BB

NEW SINGLE FAMILY RESIDENCE
407 DALLAS DRIVE
CAMPBELL, CA 95008

Revision Schedule


NO.	DATE	DESCRIPTION

Architectural, Cross Sections, AA & BB


A300

SCALE AS INDICATED

2/7/2024 10:39:10 AM



1 Cross Section, CC
1/4" = 1'-0"




2 Cross Section, DD
1/4" = 1'-0"

SECTION KEYNOTES

- 1 STANDING SEAM METAL ROOF
- 2 RADIANT BARRIER ROOF SHEATHING
- 3 HEADER, SEE STRUCTURAL
- 4 CONCRETE SLAB
- 5 2X TYP. FASCIA BOARD PRE-PRIMED/ PAINTED
- 6 ENGINEERED BEAM, SEE STRUCTURAL
- 7 FIRE STOP
- 8 R-19 INSULATION @ ALL RAISED FLOOR AREA
- 9 R-21 INSULATION @ PERIMETER WALLS
- 10 R-38 INSULATION @ CEILING
- 11 R-38 RIGID INSULATION, SPRAY FOAM @ VAULTED CEILING
- 12 SKYLIGHT
- 13 TYP. 24 GA. GALV. SHEET METAL GUTTER & DOWN SPOUT
- 14 ROOF PITCH TO MATCH / SYMMETRICAL
- 15 FOUNDATION, SEE STRUCTURAL
- 16 FLOOR JOISTS, SEE STRUCTURAL
- 17 5/8" TYPE X GYPSUM

STAIRS NOTES

1. THE RISER HEIGHT SHALL BE NOT MORE THAN 7 3/4 INCHES. THE RISER SHALL BE MEASURED VERTICALLY BETWEEN LEADING EDGES OF THE ADJACENT TREADS. (CRC - R311.7.5.1)
2. THE TREAD DEPTH SHALL BE NOT LESS THAN 10 INCHES. THE TREAD DEPTH SHALL BE MEASURED HORIZONTALLY BETWEEN THE VERTICAL PLANES OF THE FOREMOST PROJECTION OF ADJACENT TREADS AND AT A RIGHT ANGLE TO THE TREAD'S LEADING EDGE. (CRC - R311.7.5.2)
3. HANDRAILS SHALL NOT BE LESS THAN 34" OR MORE THAN 38" IN HEIGHT ABOVE THE STAIR NOSING. HANDRAILS SHALL BE CONTINUOUS PER FLIGHT OF STAIRS. HANDRAILS SHALL BE 1-1/2" CLR. OF ALL ADJACENT FIN. MATTS AND ENDS SHALL RETURN TO OR TERMINATE IN NEWEL POSTS OR SAFE TERMINALS. HANDRAILS SHALL BE 1-1/4" IN CROSS-SECTIONAL DIMENSION OR APPROVED EQUAL AND BE SMOOTH WITH NO SHARP EDGES/COR. STAIR & RAILING SUPPLIER SHALL SATISFY ALL BUILDING DEPARTMENT APPROVAL REQUIREMENTS FOR THE PRODUCTS THEY PROVIDE OR INSTALL.
4. THE GURADRILL CONST. SHALL BE ABLE TO RESIST A LOAD OF 20 LBS PER LIN. FT. APPLIED HORIZONTALLY ALONG THE RAIL. REQUIRED GUARDS SHALL NOT HAVE OPENINGS THAT ALLOW THE PASSAGE OF A SPHERE 4 INCHES IN DIAMETER FROM THE WALKING SURFACE REQUIRED GUARD HEIGHT. (CBC 1015.4)
5. FOR OCCUPANCIES IN GROUP R-3, WHERE TOP OF THE GUARD SERVES AS A HANDRAIL ON THE OPEN SIDES OF STAIRS, THE TOP OF THE GUARD SHALL NOT BE LESS THAN 34 INCHES AND NOT MORE THAN 38 INCHES MEASURED VERTICALLY FROM A LINE CONNECTING THE LEADING EDGES OF THE TREADS. (CBC 1015.3)
6. THE HANDRAIL CONSTRUCTION SHALL BE ABLE TO RESIST A LOAD OF 200 LBS APPLIED IN ANY DIRECTIONS AT ANY POINT ALONG THE TOP RAIL.
7. WHERE HANDRAILS ARE NOT CONTINUOUS BETWEEN FLIGHTS, THE HANDRAILS SHALL EXTEND HORIZONTALLY NOT LESS THAN 12 INCHES BEYOND THE TOP RISER AND CONTINUE TO SLOPE FOR THE DEPTH OF ONE TREAD BEYOND THE BOTTOM RISER. THE EXTENSIONS OF HANDRAILS SHALL BE IN THE SAME DIRECTION OF THE FLIGHTS OF STAIRS AT STAIRWAYS. (CBC 1014.6)
8. HANDRAIL GRASPABILITY (CBC 1014.3)
 - A. TYPE I- HANDRAILS WITH A CIRCULAR CROSS SECTION SHALL HAVE AN OUTSIDE DIAMETER OF NOT LESS THAN 1 1/4 INCHES (32 MM) AND NOT GREATER THAN 2 INCHES (51 MM). WHERE THE HANDRAIL IS NOT CIRCULAR, IT SHALL HAVE A PERIMETER DIMENSION OF NOT LESS THAN 4 INCHES (102 MM) AND NOT GREATER THAN 6 1/4 INCHES (160 MM) WITH A MAXIMUM CROSS-SECTIONAL DIMENSION OF 2 1/4 INCHES (57 MM) AND MINIMUM CROSS-SECTIONAL DIMENSION OF 1 INCH (25 MM). EDGES SHALL HAVE A MINIMUM RADIUS OF 0.01 INCH (0.25 MM).
 - B. TYPE II- HANDRAILS WITH A PERIMETER GREATER THAN 6 1/4 INCHES (160 MM) SHALL PROVIDE A GRASPABLE FINGER RECESS AREA ON BOTH SIDES OF THE PROFILE. THE FINGER RECESS SHALL BEGIN WITHIN A DISTANCE OF 3/4 INCH (19 MM) MEASURED VERTICALLY FROM THE TALLEST PORTION OF THE PROFILE AND ACHIEVE A DEPTH OF NOT LESS THAN 5/16 INCH (8 MM) WITHIN 7/8 INCH (22 MM) BELOW THE WIDEST PORTION OF THE PROFILE. THIS REQUIRED DEPTH SHALL CONTINUE FOR NOT LESS THAN 3/8 INCH (10 MM) TO A LEVEL THAT IS NOT LESS THAN 13/4 INCHES (45 MM) BELOW THE TALLEST PORTION OF THE PROFILE. THE WIDTH OF THE HANDRAIL ABOVE THE RECESS SHALL BE NOT LESS THAN 1 1/4 INCHES (32 MM) TO NOT GREATER THAN 2 3/4 INCHES (70 MM). EDGES SHALL HAVE A MINIMUM RADIUS OF 0.01 INCH (0.25 MM).



GORDON K WONG, ARCHITECT LIC# 34045
1000 WILSON AVENUE SUITE 100
CAMPBELL, CA 95008
GORDONKWONG@GKWAARCHITECTS.COM

GORDON K WONG, ARCHITECT LIC# 34045
1000 WILSON AVENUE SUITE 100
CAMPBELL, CA 95008
GORDONKWONG@GKWAARCHITECTS.COM



Architectural, Cross Sections, CC & DD

NEW SINGLE FAMILY RESIDENCE
401 DALLAS DRIVE
CAMPBELL, CA 95008

Revision Schedule

NO.	DATE	DESCRIPTION

Architectural,
Cross Sections,
CC & DD


A301

SCALE AS INDICATED

2/7/2024 10:39:14 AM



Architectural, 3D Model



JOSHUA LIU & KEVIN YU, PROJECT DESIGNERS
 1500 SULLY AVENUE SUITE 100
 CAMPBELL, CA 95008
 JOSHUALIU@GKWARCHITECTS.COM

GORDON K WONG, ARCHITECT LIC# 34045
 1500 SULLY AVENUE SUITE 100
 CAMPBELL, CA 95008
 GORDONKWONG@GKWARCHITECTS.COM



NEW SINGLE FAMILY RESIDENCE
 407 DALLAS DRIVE
 CAMPBELL, CA 95008

Revision Schedule

NO.	DESCRIPTION	DATE

Architectural, 3D Model

A600

SCALE AS INDICATED

2/7/2024 10:39:54 AM