



## Plan Submittal - Residential Garage Conversions

Feb 2014

### Purpose

This handout establishes a procedure for complete plan review submittals when an existing garage in a single-family dwelling is converted to a habitable area (i.e., living room, bedroom, playroom, etc.). According to current code regulations (2013 California Building Code), permits are required when buildings are constructed, altered or improved. Therefore, the following guideline shall be reviewed before commencing any work.

### Permits Required

A building permit is required for the following type of work:

- Complete attached and detached garage conversion to living space(s)
- Partial garage conversions to living space(s)

### Plan Submittal for Construction

#### Quantity

- Three (3) sets of plans must be submitted; a completed Application for Permit form and plan check fee paid. Upon submittal of plans, they will be distributed to Building Inspection & Safety and Planning for review.
- Two (2) sets of "wet-signed" and stamped calculation reports prepared by a professional engineer licensed in the State of California (if required).
- Two (2) sets of Title 24 energy reports.

#### Additional Requirements

- **Campbell Unified School Districts** collects Developer Fees for residential additions – similarly, for conversions to habitable areas - in excess of 500 square feet; the fees are collected by the district prior to permit issuance.

Forms will be provided by Campbell Building & Safety during the plan review process.

### Plan Review Timelines

Allow a minimum of **fifteen** business days for the first plan review and **five** business days for all other subsequent reviews.

*Note: the plan review time may be extended depending on the complexity and size of the structure.*

### Minimum Plan Requirements

#### Size

Minimum 11" x 17" and maximum 24" x 36" plans drawn to scale (i.e., floor plan: ¼" = 1' - 0", site plan: 1" = 20' - 0"), fully dimensioned, clear and legible. Single line floor plans are unacceptable.

*NOTE: Multiple types of information can be combined on plans if clarity is maintained. This is not a complete list of all design requirements; additional information may be required after the plan review.*

#### Information

1. Cover sheet - legal job address and APN (assessors parcel number); name, address and phone number of owner, contractor and contact person; name, address and phone number, title and registration information of project design professional; description of work including current applicable codes, type of construction (V-N), occupancy classifications for single family dwelling/garage (R-3/U-1), if installing / modifying a fire sprinkler system; total building area (sq. ft. breakdown for dwelling, garage, porches); zoning; index of drawings.
2. Plot plan - lot dimension and parcel size; building location with all setback distances to property lines, easements and other buildings;

north arrow; location of gas/electrical/water meters; septic/well systems (as applicable).

3. Architectural plans - floor plan layout showing existing and proposed uses; existing and proposed door/window types and sizes; minimum of two exterior elevations identifying finish materials, colors, and interior wall covering.

*For partial conversions when a garage space(s) will be maintained:* show location and fire-rating detail of **1-hr occupancy separation wall**. 1) The garage shall be separated and its attic area by a min. ½” gypsum board applied to the garage side (Garages beneath habitable rooms shall use a min. 5/8” Type X gypsum board or equivalent and 2) 1-3/8” thick, self-closing, solid wood door or 20-minute, self-closing door; and 3) Min. 0.019” sheet metal for ducting penetration within the 1-hr wall.

*When the conversion includes a bedroom:* show location of smoke detector(s) and Carbon Monoxide Alarms; emergency egress clear openings of 5.7 sq. ft., 24” opening height, 20” opening width, and not more than 44” above floor opening directly to street/yard.

*For all other habitable spaces:* show source of natural light/ventilation (min. of 8%/4% of floor area)

4. Structural plans - any proposed floor/wall/roof framing plan should include direction of framing, size (e.g., 2’ x 8’), spacing (16” on center), span (length between supports), and location/size of opening supports (headers).

Shear wall OR braced wall panel schedule, location, length and detail references. If filling the existing garage door opening with a new wall, show an entire wall framing detail from foundation to roof members depicting load-path connections; bracing type; ceiling/wall/floor insulation values; ceiling height dimension. Provide a slab foundation detail with added supports if garage stem wall is retrofitted.

*\*Refer to the “**Conventional Light-Frame Bracing**” handout for non-engineered building designs and specific requirements.*

**Light Wood-Frame Construction:** *Plans for single family dwellings of light wood-frame construction (as defined by Section 2308 of the 2013 CBC) may be prepared by any person, if the structure consists of not more than two stories and basement in height. However, if the structure has unusual design features and deviates from conventional light-frame standards, it shall be designed following*

*engineering standards. Engineered plans shall therefore be prepared by a professional architect or engineer, licensed in the State of California.*

5. Mechanical, Electrical and Plumbing plans - identify size and location of main and sub-panels; receptacle outlets (arc-fault circuit interrupter, combination type) installed to provide protection of the branch circuit. Required GFCI locations (in bathrooms), switches, light fixtures; plumbing fixtures; duct layout.

*\*For new bathrooms:* refer to the “**Residential Bathroom Remodel**” handout for specific requirements. A set of plans will be required to go to West Valley Sanitation Department located at 100 E Sunnyside, Campbell CA **Phone (408) 378-2407**

6. Energy compliance demonstration – for areas that are now conditioned. The energy compliance forms CF-1R and MF-1 shall be completed, signed and affixed to plans.

*\*The “**Alternate Package ‘D’ for Residential Additions**” is available for home owners wishing to complete their own Energy Conservation Measures documentation. The package however, is limited to a few garage conversion projects; a computer generated energy report is therefore required for most other garage conversion cases.*

7. Campbell Zoning Code (Article 3, Chapter 21.28.040 Table 3-1) requires a certain amount of on-site covered or enclosed parking spaces be provided. The addition of parking spaces must be depicted in the construction drawings. Please contact a planner at (408) 866-2140 for additional information.

## Fees

Building fees are based on the total value of all construction work (including labor and materials). Consult with a permit technician for details.

## Application Forms


An Application for Permit form may be requested at the Building Safety & Inspection office located at:

Address: **8401 Laguna Palms Way**  
Phone: **(916) 478-2235**  
Hours: **8 am – 5 pm Monday – Friday**

# Sample Details of 1-Hour Occupancy Separation Wall/Ceiling

(This sheet is for information and reference only and is not a substitute for accurate drawings prepared for each proposed construction project)

## RESIDENCE



### A. Cross-Section through Garage

<b>Floor / Ceiling Construction</b>	<b>1-Hour Construction</b>
Floor Joists - 2 Story	One layer of 5/8" Type "X" Gypsum Board (Reference: CBC 406.1A #1)
<b>Roof / Ceiling Construction</b>	<b>1-Hour Construction</b>
Ceiling Joists – 1 Story	One layer of 1/2" Gypsum Board (Reference: CBC 406.1.4 #1)

Plywood Sheathing

Floor Joist, "TJI" or Trusses  
must be minimum depth of 10"

One layer 5/8" Type 'X' Gypsum  
Board; stagger joints  
(or provide approved listing)

### C. Typical Floor / Ceiling Assembly